


General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

PPAK5X6 Pin Configuration



BVDSS	RDS(ON)	ID
150V	22mΩ	60A

Features

- 150V,60A, RDS(ON) =22mΩ @VGS = 10V
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

Applications

- Motor Drive
- Power Tools
- LED Lighting

Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	150	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current – Continuous ($T_c=25^\circ\text{C}$)	60	A
	Drain Current – Continuous ($T_c=100^\circ\text{C}$)	38	A
I_{DM}	Drain Current – Pulsed ¹	240	A
EAS	Single Pulse Avalanche Energy ²	76	mJ
IAS	Single Pulse Avalanche Current ²	39	A
P_D	Power Dissipation ($T_c=25^\circ\text{C}$)	205	W
	Power Dissipation – Derate above 25°C	1.64	W/ $^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	0.61	$^\circ\text{C}/\text{W}$



150V N-Channel MOSFETs

PDC60ND15BHX**Electrical Characteristics ($T_J=25\text{ }^{\circ}\text{C}$, unless otherwise noted)****Off Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}$, $I_D=250\mu\text{A}$	150	---	---	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=120\text{V}$, $V_{GS}=0\text{V}$, $T_J=25\text{ }^{\circ}\text{C}$	---	---	1	μA
		$V_{DS}=120\text{V}$, $V_{GS}=0\text{V}$, $T_J=85\text{ }^{\circ}\text{C}$	---	---	10	μA
I_{GSS}	Gate-Source Leakage Current	$V_{GS}=\pm 20\text{V}$, $V_{DS}=0\text{V}$	---	---	± 100	nA

On Characteristics

$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance ³	$V_{GS}=10\text{V}$, $I_D=20\text{A}$	---	18	22	$\text{m}\Omega$
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{GS}=V_{DS}$, $I_D=250\mu\text{A}$	2.5	3.5	4.5	V

Dynamic and switching Characteristics³







Q_g	Total Gate Charge	$V_{DS}=75\text{V}$, $V_{GS}=10\text{V}$, $I_D=30\text{A}$	---	34	50	nC
Q_{gs}	Gate-Source Charge		---	5.5	9	
Q_{gd}	Gate-Drain Charge		---	11.5	18	
$T_{d(on)}$	Turn-On Delay Time	$V_{DD}=75\text{V}$, $V_{GS}=10\text{V}$, $R_G=6\Omega$ $I_D=30\text{A}$	---	6	10	ns
T_r	Rise Time		---	9	15	
$T_{d(off)}$	Turn-Off Delay Time		---	8	12	
T_f	Fall Time		---	12	18	
C_{iss}	Input Capacitance	$V_{DS}=75\text{V}$, $V_{GS}=0\text{V}$, $F=1\text{MHz}$	---	1690	2550	pF
C_{oss}	Output Capacitance		---	150	230	
C_{rss}	Reverse Transfer Capacitance		---	7	11	
R_g	Gate Resistance	$V_{GS}=0\text{V}$, $V_{DS}=0\text{V}$, $F=1\text{MHz}$	---	0.5	---	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	60	A
I_{SM}	Pulsed Source Current		---	---	120	A
V_{SD}	Diode Forward Voltage	$V_{GS}=0\text{V}$, $I_s=1\text{A}$, $T_J=25\text{ }^{\circ}\text{C}$	---	---	1	V
t_{rr}	Reverse Recovery Time	$V_R=100\text{V}$, $I_s=10\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$, $T_J=25\text{ }^{\circ}\text{C}$	---	65	---	ns
Q_{rr}	Reverse Recovery Charge		---	210	---	nC

Note :

- Repetitive Rating : Pulsed width limited by maximum junction temperature.
- $V_{DD}=50\text{V}$, $L=0.1\text{mH}$, $I_{AS}=39\text{A}$, $R_G=25\Omega$, Starting $T_J=25\text{ }^{\circ}\text{C}$.
- Essentially independent of operating temperature.


Fig.1 Typical Output Characteristics

Fig.2 Continuous Drain Current vs. T_c

Fig.3 Normalized RDSON vs. T_j

Fig.4 Normalized V_{th} vs. T_j

Fig.5 Turn-On Resistance vs. V_{GS}

Fig.6 Turn-On Resistance vs. I_D









Fig.7 Capacitance Characteristics

Fig.8 Gate Charge Characteristics

Fig.9 Normalized Transient Impedance

Fig.10 Maximum Safe Operation Area

Fig.11 Switching Time Waveform

Fig.12 Gate Charge Waveform

PPAK5x6 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	1.200	0.850	0.047	0.031
b	0.510	0.300	0.020	0.012
C	0.300	0.200	0.012	0.008
D1	5.400	4.800	0.212	0.189
D2	4.310	3.610	0.170	0.142
E	6.300	5.850	0.248	0.230
E1	5.960	5.450	0.235	0.215
E2	3.920	3.300	0.154	0.130
e	1.27BSC		0.05BSC	
H	0.650	0.380	0.026	0.015
K	---	1.100	---	0.043
L	0.710	0.380	0.028	0.015
L1	0.250	0.050	0.009	0.002
θ	12°	0°	12°	0°

PPAK5X6 RECOMMENDED LAND PATTERN

unit : mm