

General Description


These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDS(ON)	ID
65V	4.9mΩ	95A

Features

- 65V,95A, $RDS(ON) = 4.9m\Omega @ VGS = 10V$
- Improved dv/dt capability
- Fast switching
- Green Device Available

PPAK5X6 Pin Configuration



Applications

- Networking
- Load Switch
- LED applications

Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	65	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current – Continuous ($T_c=25^\circ C$)	95	A
	Drain Current – Continuous ($T_c=100^\circ C$)	60	A
I_{DM}	Drain Current – Pulsed ¹	380	A
EAS	Single Pulse Avalanche Energy ²	151.3	mJ
IAS	Single Pulse Avalanche Current ²	55	A
P_D	Power Dissipation ($T_c=25^\circ C$)	96	W
	Power Dissipation – Derate above 25°C	0.77	W/°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
T_J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	°C/W
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	1.3	°C/W

Electrical Characteristics (T_J=25 °C, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250µA	65	---	---	V
I _{DSS}	Drain-Source Leakage Current	V _{DS} =60V, V _{GS} =0V, T _J =25°C	---	---	1	µA
		V _{DS} =48V, V _{GS} =0V, T _J =85°C	---	---	10	µA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±20V, V _{DS} =0V	---	---	±100	nA

On Characteristics

R _{Ds(ON)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =20A	---	4.1	4.9	mΩ
		V _{GS} =4.5V, I _D =15A	---	6.2	8.1	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250µA	1.2	1.6	2.5	V
g _{fS}	Forward Transconductance	V _{DS} =10V, I _D =3A	---	10	---	S

Dynamic and switching Characteristics

Q _g	Total Gate Charge ^{3, 4}	V _{DS} =48V, V _{GS} =10V, I _D =30A	---	36	54	nC
Q _{gs}	Gate-Source Charge ^{3, 4}		---	4.7	7.1	
Q _{gd}	Gate-Drain Charge ^{3, 4}		---	13.5	20	
T _{d(on)}	Turn-On Delay Time ^{3, 4}	V _{DD} =48V, V _{GS} =10V, R _G =6Ω I _D =1A	---	10.2	15	ns
T _r	Rise Time ^{3, 4}		---	16	24	
T _{d(off)}	Turn-Off Delay Time ^{3, 4}		---	42	63	
T _f	Fall Time ^{3, 4}		---	38	57	
C _{iss}	Input Capacitance	V _{DS} =48V, V _{GS} =0V, F=1MHz	---	1675	2510	pF
C _{oss}	Output Capacitance		---	322	485	
C _{rss}	Reverse Transfer Capacitance		---	14	25	
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz	---	1.2	---	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _s	Continuous Source Current	V _G =V _D =0V, Force Current	---	---	95	A
I _{SM}	Pulsed Source Current		---	---	190	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _s =1A, T _J =25°C	---	---	1	V
t _{rr}	Reverse Recovery Time ³	V _R =50V, I _s =10A di/dt=100A/µs, T _J =25°C	---	54	---	ns
Q _{rr}	Reverse Recovery Charge ³		---	67	---	nC

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=25V, V_{GS}=10V, L=0.1mH, I_{AS}=55A., R_G=25Ω, Starting T_J=25°C.
3. The data tested by pulsed, pulse width ≤ 300µs, duty cycle ≤ 2%.
4. Essentially independent of operating temperature.










Fig.1 Continuous Drain Current vs. Tc

Fig.2 Normalized RDSON vs. Tj

Fig.3 Normalized Vth vs. Tj

Fig.4 Gate Charge Characteristics

Fig.5 Normalized Transient Impedance

Fig.6 Maximum Safe Operation Area



Fig.7 Switching Time Waveform

Fig.8 Gate Charge Waveform

PPAK5x6 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	1.200	0.850	0.047	0.031
b	0.510	0.300	0.020	0.012
C	0.300	0.200	0.012	0.008
D1	5.400	4.800	0.212	0.189
D2	4.310	3.610	0.170	0.142
E	6.300	5.850	0.248	0.230
E1	5.960	5.450	0.235	0.215
E2	3.920	3.300	0.154	0.130
e	1.27BSC		0.05BSC	
H	0.650	0.380	0.026	0.015
K	---	1.100	---	0.043
L	0.710	0.380	0.028	0.015
L1	0.250	0.050	0.009	0.002
θ	12°	0°	12°	0°

PPAK5X6 RECOMMENDED LAND PATTERN



unit : mm