


General Description

These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

SOP8 Dual Pin Configuration



BVDSS	RDS(ON)	ID
-40V	40mΩ	-4.6A

Features

- -40V, -4.6A, RDS(ON) = 40mΩ@VGS = -10V
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

Applications

- Motor Drive
- Power Tools
- LED Lighting

Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	-40	V
V _{Gs}	Gate-Source Voltage	± 20	V
I _D	Drain Current – Continuous ($T_A=25^\circ\text{C}$)	-4.6	A
	Drain Current – Continuous ($T_A=70^\circ\text{C}$)	-3.7	A
I _{DM}	Drain Current – Pulsed ¹	-18.4	A
EAS	Single Pulse Avalanche Energy ²	36.5	mJ
I _{AS}	Single Pulse Avalanche Current ²	27	A
P _D	Power Dissipation ($T_c=25^\circ\text{C}$)	1.47	W
	Power Dissipation – Derate above 25°C	0.011	W/°C
T _{STG}	Storage Temperature Range	-50 to 150	°C
T _J	Operating Junction Temperature Range	-50 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance Junction to ambient	---	85	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=250\mu\text{A}$	-40	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BV_{DSS} Temperature Coefficient	Reference to 25°C , $I_D=-1\text{mA}$	---	-0.02	---	$\text{V}/^\circ\text{C}$
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=-40\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	1	μA
		$V_{\text{DS}}=-32\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=125^\circ\text{C}$	---	---	10	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 20\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA

On Characteristics

$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=-10\text{V}$, $I_D=-2.5\text{A}$	---	33	40	$\text{m}\Omega$
		$V_{\text{GS}}=-10\text{V}$, $I_D=-2.5\text{A}$ ($T_J=125^\circ\text{C}$)	---	47.5	---	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}$, $I_D=-2\text{A}$	---	46	65	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_D=250\mu\text{A}$	1.2	1.8	2.5	V
$\Delta V_{\text{GS(th)}}$	$V_{\text{GS(th)}}$ Temperature Coefficient		---	4.18	---	$\text{mV}/^\circ\text{C}$
g_{fs}	Forward Transconductance	$V_{\text{DS}}=-10\text{V}$, $I_D=-1\text{A}$	---	4	---	S

Dynamic and switching Characteristics

Q_g	Total Gate Charge ^{3, 4}	$V_{\text{DS}}=-20\text{V}$, $V_{\text{GS}}=-10\text{V}$, $I_D=-2\text{A}$	---	16.2	32	nC
Q_{gs}	Gate-Source Charge ^{3, 4}		---	1.9	4	
Q_{gd}	Gate-Drain Charge ^{3, 4}		---	3.4	6.5	
$T_{\text{d(on)}}$	Turn-On Delay Time ^{3, 4}	$V_{\text{DD}}=-20\text{V}$, $V_{\text{GS}}=-10\text{V}$, $R_G=6\Omega$ $I_D=1\text{A}$	---	12	24	ns
T_r	Rise Time ^{3, 4}		---	13.2	26	
$T_{\text{d(off)}}$	Turn-Off Delay Time ^{3, 4}		---	46.8	90	
T_f	Fall Time ^{3, 4}		---	20.4	40	
C_{iss}	Input Capacitance	$V_{\text{DS}}=-20\text{V}$, $V_{\text{GS}}=0\text{V}$, $F=1\text{MHz}$	---	1090	2180	pF
C_{oss}	Output Capacitance		---	100	200	
C_{rss}	Reverse Transfer Capacitance		---	76	150	
R_g	Gate resistance	$V_{\text{GS}}=0\text{V}$, $V_{\text{DS}}=0\text{V}$, $F=1\text{MHz}$	---	16	---	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	-4.6	A
I_{SM}	Pulsed Source Current		---	---	-9.2	A
V_{SD}	Diode Forward Voltage	$V_{\text{GS}}=0\text{V}$, $I_s=-1\text{A}$, $T_J=25^\circ\text{C}$	---	---	-1	V
t_{rr}	Reverse Recovery Time		---	91.8	---	nS
Q_{rr}	Reverse Recovery Charge	$T_J=25^\circ\text{C}$	---	51.3	---	nC

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. $V_{\text{DD}}=25\text{V}$, $V_{\text{GS}}=-10\text{V}$, $L=0.1\text{mH}$, $I_{\text{AS}}=27\text{A}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$.
3. The data tested by pulsed , pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
4. Essentially independent of operating temperature.








Fig.1 Continuous Drain Current vs. T_J

Fig.2 Normalized $R_{DS(on)}$ vs. T_J

Fig.3 Normalized V_{th} vs. T_J

Fig.4 Gate Charge Waveform








Fig.5 Typical Output Characteristics

Fig.6 Turn-On Resistance vs. Id

Fig.7 Capacitance Characteristics

Fig.8 Normalized Transient Impedance

Fig.10 Switching Time Waveform
Fig.9 Maximum Safe Operation Area

Fig.11 EAS Waveform

SOP8 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.068
A1	0.100	0.250	0.004	0.009
A2	1.300	1.500	0.052	0.059
A3	0.600	0.700	0.024	0.027
b	0.390	0.480	0.016	0.018
c	0.210	0.260	0.009	0.010
D	4.700	5.100	0.186	0.200
E	5.800	6.200	0.229	0.244
E1	3.700	4.100	0.146	0.161
e	1.270(BSC)		0.050(BSC)	
h	0.250	0.500	0.010	0.019
L	0.500	0.800	0.019	0.031
L1	1.050(BSC)		0.041(BSC)	

