


General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

SOP8 Pin Configuration



BVDSS	RDS(ON)	ID
65V	11.3mΩ	8.8A

Features

- 65V, 8.8A, $RDS(ON) = 11.3m\Omega$ @ $VGS = 10V$
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

Applications

- Motor Drive
- Power Tools
- LED Lighting
- Quick Charger

Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	65	V
V_{GS}	Gate-Source Voltage	+20/-12	V
I_D	Drain Current – Continuous ($T_A=25^\circ C$)	8.8	A
	Drain Current – Continuous ($T_A=70^\circ C$)	7.0	A
I_{DM}	Drain Current – Pulsed ¹	35.2	A
EAS	Single Pulse Avalanche Energy ²	51.2	mJ
IAS	Single Pulse Avalanche Current ²	32	A
V_{SPIKE}	V_{DS} spike voltage ($\leq 100ns$) ⁵	80	V
P_D	Power Dissipation ($T_c=25^\circ C$)	1.47	W
	Power Dissipation – Derate above $25^\circ C$	0.01	W/ $^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	85	$^\circ C/W$

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=250\mu\text{A}$	65	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BV_{DSS} Temperature Coefficient	Reference to 25°C , $I_D=1\text{mA}$	---	0.03	---	$\text{V}/^\circ\text{C}$
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=60\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	1	μA
		$V_{\text{DS}}=48\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=85^\circ\text{C}$	---	---	10	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=+20\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	100	nA

On Characteristics

$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance ³	$V_{\text{GS}}=10\text{V}$, $I_D=4\text{A}$	---	9.4	11.3	$\text{m}\Omega$
		$V_{\text{GS}}=10\text{V}$, $I_D=4\text{A}$ ($T_J=125^\circ\text{C}$)	---	14.1	---	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}$, $I_D=3\text{A}$	---	15.6	20.5	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_D=250\mu\text{A}$	1	1.6	2.5	V
$\Delta V_{\text{GS(th)}}$	$V_{\text{GS(th)}}$ Temperature Coefficient		---	-5	---	$\text{mV}/^\circ\text{C}$
g_{fs}	Forward Transconductance	$V_{\text{DS}}=10\text{V}$, $I_D=3\text{A}$	---	6	---	S

Dynamic and switching Characteristics







Q_g	Total Gate Charge ^{3, 4}	$V_{\text{DS}}=30\text{V}$, $V_{\text{GS}}=10\text{V}$, $I_D=6\text{A}$	---	15.3	30.6	nC
Q_{gs}	Gate-Source Charge ^{3, 4}		---	2.4	5.8	
Q_{gd}	Gate-Drain Charge ^{3, 4}		---	5.4	10.8	
$T_{\text{d(on)}}$	Turn-On Delay Time ^{3, 4}	$V_{\text{DD}}=30\text{V}$, $V_{\text{GS}}=10\text{V}$, $R_G=3.3\Omega$ $I_D=1\text{A}$	---	10	20	ns
T_r	Rise Time ^{3, 4}		---	13.5	27	
$T_{\text{d(off)}}$	Turn-Off Delay Time ^{3, 4}		---	28	56	
T_f	Fall Time ^{3, 4}		---	20	40	
C_{iss}	Input Capacitance		---	945	1890	pF
C_{oss}	Output Capacitance	$V_{\text{DS}}=30\text{V}$, $V_{\text{GS}}=0\text{V}$, $F=1\text{MHz}$	---	275	550	
C_{rss}	Reverse Transfer Capacitance		---	26	52	
R_g	Gate resistance	$V_{\text{GS}}=0\text{V}$, $V_{\text{DS}}=0\text{V}$, $F=1\text{MHz}$	---	0.3	---	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$8I_S$	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	8.8	A
I_{SM}	Pulsed Source Current ³		---	---	17.6	A
V_{SD}	Diode Forward Voltage ³	$V_{\text{GS}}=0\text{V}$, $I_S=1\text{A}$, $T_J=25^\circ\text{C}$	---	---	1	V
t_{rr}	Reverse Recovery Time	$V_{\text{GS}}=0\text{V}$, $I_S=5\text{A}$, $di/dt=100\text{A}/\mu\text{s}$ $T_J=25^\circ\text{C}$	---	29.5	---	ns
Q_{rr}	Reverse Recovery Charge		---	30.4	---	nC

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. $V_{\text{DD}}=50\text{V}$, $V_{\text{GS}}=10\text{V}$, $L=0.1\text{mH}$, $I_{\text{AS}}=32\text{A}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$.
3. The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
4. Essentially independent of operating temperature.
5. The spike duty cycle 1% max., limited by $T_J(\text{max})=125^\circ\text{C}$


Fig.1 Continuous Drain Current vs. T_J

Fig.2 Normalized $R_{DS(ON)}$ vs. T_J

Fig.3 Normalized V_{th} vs. T_J

Fig.4 Gate Charge Waveform

Fig.5 Typical Output Characteristics

Fig.6 Turn-On Resistance vs. I_D



 V_{DS}, Drain to Source Voltage (V)



Fig.7 Capacitance Characteristics

 V_{GS}, Gate to Source Voltage (V)

Fig.8 Transfer Characteristics


Square Wave Pulse Duration (s)





Fig.9 Normalized Transient Response

 V_{DS}, Drain to Source Voltage (V)

Fig.10 Maximum Safe Operation

Fig.11 Switching Time Waveform

Fig.12 EAS Waveform

SOP8 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.068
A1	0.100	0.250	0.004	0.009
A2	1.300	1.500	0.052	0.059
A3	0.600	0.700	0.024	0.027
b	0.390	0.480	0.016	0.018
c	0.210	0.260	0.009	0.010
D	4.700	5.100	0.186	0.200
E	5.800	6.200	0.229	0.244
E1	3.700	4.100	0.146	0.161
e	1.270(BSC)		0.050(BSC)	
h	0.250	0.500	0.010	0.019
L	0.500	0.800	0.019	0.031
L1	1.050(BSC)		0.041(BSC)	
θ	0°	8°	0°	8°